



More information to help with exit hardware selection is available on our web page

Briton 378

Push Bar Panic Latch

TESTED & CERTIFIED TO EN 1125 & EN 1634



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors 665mm to 1300mm wide and up to 2500mm high
- Supplied right hand (latch reversible on site)
- One point locking for security
- Rim panic latch with single point locking
- Suitable for single doors and double rebated doors when used in combination with Briton 376 panic bolt and 378DDS double door strike



Briton 376

Push Bar Panic Bolt

TESTED & CERTIFIED TO EN 1125 & EN 1634



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors 665mm to 1300mm wide and up to 2500mm high.
- Supplied right hand (latch reversible on site)
- Two-point locking for extra security
- Anti-thrust device, prevents forced latch retraction
- Adjustable top & bottom shoots
- Supplied with easy clean socket
- Suitable for single doors and double rebated doors when used in combination with Briton 378 panic latch and 378DDS double door strike



Briton 377

Push Bar Panic for Double Rebated Doors

TESTED & CERTIFIED TO EN 1125 & EN 1634



For Double Rebated Doors

- Suitable for use on double fire & smoke doors 1330mm to 2600mm wide and up to 2500mm high.
- Supplied right hand (latch reversible on site)
- Three-point locking for extra security
- Anti-thrust device, prevents forced latch retraction
- Comprises of Briton 376 vertical panic bolt, 378 reversible rim panic latch and 378DDS double door strike in one convenient pack
- Adjustable top & bottom shoots



Briton 379.N

Push Bar Panic with Mortice Nightlatch

TESTED & CERTIFIED TO EN 1125 & EN 1634



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors 665mm to 1300mm wide and up to 2500mm high.
- Supplied right hand (latch reversible on site)
- One point locking for security
- Supplied with dual profile cylinder mortice nightlatch, accepts both euro and oval profile cylinders (cylinder not supplied)
- Anti-thrust device, prevents forced latch retraction
- Suitable for non-rebated double doors when used in combination with Briton 376 Panic bolt and 378DDS double door strike



Briton 1438

Push Pad Emergency Latch

TESTED & CERTIFIED TO EN 179 & EN 1634



For Single & Double Rebated Doors

- Pad operated rim latch
- Suitable for use on single doors and the first opening leaf of double rebated doors when used in combination with Briton 372 vertical bolt device and 378DDS double door strike
- One point locking for security
- Supplied right hand (latch reversible on site)
- Can be used with a rim cylinder fitted to the outside of the door



Briton 372

Push Pad Emergency Bolt

TESTED & CERTIFIED TO EN 179 & EN 1634



For Single & Double Non Rebated Doors

- Suitable for use on fire & smoke doors 665mm to 1300mm wide and up to 2500mm high
- Two-point locking for extra security
- Double vertical bolts - self handed
- Anti-thrust device, prevents forced latch retraction
- Adjustable top & bottom shoots
- Suitable for single doors and non rebated double doors when used in combination with Briton 1438 rim latch device and 378DDS double door strike



Panic Exit Hardware - EN 1125

Panic applications require an operating device that covers the width of the door. Used by members of the public it must provide a safe and effective escape with minimum effort and without prior knowledge of operation.

Typical applications:

- ✓ Shops
- ✓ Schools
- ✓ Hospitals
- ✓ Theatres & Cinemas

Emergency Exit Hardware - EN 179

Emergency applications require only a single point of operation. Used in low occupancy environments, these should only be used by trained personnel and never accessed by the public or people unfamiliar with the escape drill.

Typical applications:

- ✓ Offices
- ✓ Private Flats
- ✓ Factories
- ✓ Store/Boiler Rooms



If in doubt, always choose a product to EN 1125



Located in a PUBLIC AREA - Certified to EN 1125



Located in a NON PUBLIC AREA - Certified to EN 179



UKCA Marked to relevant BS EN Standards



CE Marked to relevant EN Standards



Certifire Approved



Fire tested to EN 1634 to achieve a rating on timber and metal doors



ISO 14025 & EN 15804 Environmental product declarations



Level of Security (1 - 3) 1, 2 or 3 point locking

Need Access from Outside?

For Single & Double Doors (fitted to the first opening leaf)

- Lever or knob operated version
- Supplied with 40mm euro profile cylinder as standard (available masterkeyed or keyed alike)
- Self handed or site reversible



1413.LE



1413.KE

For metal doors add 'M' to the ordering code e.g. 376M or 377M