

Approved body No. 1121

Certificate of constancy of performance

1121-CPR-UK-ABB7573

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

“BRITON 372 (See ANNEX A) 389 (See ANNEX B) & 1438 (See ANNEX C) Push Pad Series” Emergency Exit Devices

Intended use:- For use on single leaf escape route doors, including fire resisting control doors.

Essential characteristics	Performance	Designated Standard
Mechanical Test Evidence : WIL 539076 / WIL 539077 / WIL 539078 / WIL 539079 / WIL 539080 / WIL 539081 / WIL 539081-1 & WIL 541902 Iss 2		
Fire Test Evidence : WF 127579 / WF 417359 / WF 417361 / WF 539511/R / WF 542544/R & WF 544056 AR Iss 1		
Clause 4.2.1 Ability to release (for doors on escape routes) Release function Push pad Single doorset Double doorset Exposed edges and corners Push pad installation Operating element projection Operating element face (Push Pad) Push pad operating gap Test rod Push pad release operation Accessible gap Door free movement Top vertical bolt Covers for vertical rod Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement	< 1 sec Pass Pass Pass Pass Z < 250 mm W < 100mm Pass > 25 mm Pass Pass Pass Pass - (Annex A) NPD Pass Pass - (Annex A) Door mass ≤ 200Kg, door height ≤ 2500mm, door width ≤ 1300mm Door Height increased to 3350mm when fitted with 376ELTS/SE - Extra Long Shoot Bolts Pass Type B < 150 N Grade 4	EN 179:2008
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes) Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance – Push Pad Abuse resistance – Vertical rod Final examination	Grade 3 : 96 hours Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 500 N & 1000N 500 N - (Annex A) Type B < 150 N	

Certificate of constancy of performance

1121-CPR-UK-ABB7573

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

“BRITON 372 (See ANNEX A) 389 (See ANNEX B) & 1438 (See ANNEX C) Push Pad Series” Emergency Exit Devices

Essential characteristics	Performance	Designated Standard
Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes) Re-engagement force	< 50 N	EN 179 : 2008
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes) Durability Re-engagement force	Grade 7: 200 000 cycles < 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes) Suitability of Emergency exit devices for use on fire resisting doorsets assemblies –	Grade B : Suitable for use on fire door assemblies.	
Additional requirements		
Clause 4.1.29 Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Certificate of constancy of performance

1121-CPR-UK-ABB7573

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

“BRITON 372 (See ANNEX A) 389 (See ANNEX B) & 1438 (See ANNEX C) Push Pad Series” Emergency Exit Devices

BRITON PRODUCT CODES	DESCRIPTION	SINGLE DOOR USE	DOUBLE DOOR USE
ANNEX A – 2 Point Vertical Locking			
372.SE	Push Pad Emergency Exit With Vertical Bolts	√	√
372M.SE	Push Pad Emergency Exit With Vertical Bolts For Use With Metal Doors	√	√
ANNEX B – 1 Point Mortise latch locking			
389.SE	Push Pad Emergency Exit With Mortise Nightlatch (Cylinder Not Included)	√	√
389M.SE	Push Pad Emergency Exit With Mortise Nightlatch (Cylinder Not Included) For Use With Metal Doors	√	√
ANNEX C – 1 Point Rim Latch Locking			
1438.SE	Push Pad Emergency Exit Rim Latch	√	√
1438M.SE	Push Pad Emergency Exit Rim Latch With Metal Strike & Fixings	√	√
COMPATIBLE OUTSIDE ACCESS DEVICES			
1413.KE.SE	Outside Access Device With Knob For Use With Briton 372 & 1438 Series	√	√
1413.LE.SE	Outside Access Device With Lever For Use With Briton 372 & 1438 Series	√	√
1413.LE.SE.RO	ROBUST - Outside Access Device With Knob For Use With Briton 372 & 1438 Series	√	√
1413.KE.SE.RO	ROBUST - Outside Access Device With Lever For Use With Briton 372 & 1438 Series	√	√
ACCESSORIES			
372/1001/SE	Push Pad Main Box Assembly	√	√
370PLTM	370 Series Panic Bolt Pullman fixing kit (376/372) Timber/Metal x2 pullmans plus instruction plus strikes/screws	√	√
376/416/50	End Plug	√	√
376/931/SE	Pullman Assembly x 1 for replacement	√	√
379/931/SS	Night latch lock case	√	√
379/1011/SE	Push Pad Mortise latch Box Assembly	√	√
378DDS/SE	377 Double Door Strike Timber	---	√
378MDS/SE	377 Double Door Strike Metal	---	√
376MDS/ZP	376 Metal Door Strike	√	√
379MDS/SE	379 Metal Door Strike	√	√
376ELTS/SE	Extra Long Shoot Bolts (For doors upto 3350mm)	√	√
376FFKP/ZP	Flush Face Keeper Plate	√	√

Certificate of constancy of performance

1121-CPR-UK-ABB7573

Placed on the market under the Name or Trade Mark of

**Allegion (UK) Ltd
35 Rocky Lane
Birmingham
West Midlands
B6 5RQ
United Kingdom**

and produced in the manufacturing plant

E014110-19 - E014110-20

This is coded format and the information is held by the Approved Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 179 : 2008

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **15/07/2021** and revised on **03/02/2025** and will remain valid as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

UKCA certificate valid to: **12/05/2026**



0087



Paul Duggan
Certification Manager

**Warringtonfire Testing and Certification Limited
Unit 722, The Quadrant, Birchwood Park, Warrington, WA3 6FW, UK**