

Declaration of Performance

**UK CONSTRUCTION PRODUCTS
(AMENDMENT ETC) (EU EXIT)
REGULATIONS 2020**

No. 47458032

1. Unique identification code of the product-type:

Briton 378, 378D, 378.D, 378M, 378OEM

Accessories: - 378DDS & 378MDS, Briton 1413/LE & 1413/KE, 1413.LE & 1413.KE & 1413.BP. Briton 9260 Codelock.

P816 & 816 Rim Cylinder

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the UK CPR:

Briton 378, 378D, 378.D, 378M, 378OEM

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors

Or

Escape route doors, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited
35 Rocky Lane
Aston
Birmingham
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in UK CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

EN 1125: 2008

**Notified Certification body No.1121 performed the type testing and issued test reports.
Certificate of Constancy of Performance - 1121-CPR-UK- AAA7569**

8. UK Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Designated technical Specification
Clause 4.2.1 Ability to release (for doors on escape routes)		EN 1125:2008
Release function Panic exit device mounting Exposed edges and corners Double doorset Bar installation Bar length Bar projection Bar end Operating bar face Test rod	< 1 sec Pass > 0,5 mm Pass Z < 150 mm from frame stop > 60% of max door width W < 100 mm Pass > 18 mm Pass	


Door face gap	> 25 mm
Accessible gap	Pass
Door free movement	Pass
Top vertical bolt	N/A
Keepers	Pass
Keepers dimensions	N/A
Door mass and dimensions	Door mass ≤ 200 Kg, door height ≤ 2520 mm, door width ≤ 1320 mm
Outside access device	Pass
Release forces	< 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N.
Security requirement	Grade 2
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes)	
Corrosion resistance	Grade 3: 96 h
Temperature range	Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C°
Covers for vertical rods	N/A
Lubrication	Lubrication every 20 000 cycles
Re-engagement force	< 50 N
Durability	Grade 7: 200 000 cycles
Abuse resistance –Horizontal bar	1 000 N
Abuse resistance –Vertical rod	N/A
Final examination	< 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N
Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes)	
Re-engagement force	< 50 N
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	
Durability	Grade 7: 200 000 cycles
Re-engagement force	< 50 N
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	
Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies
Control of Dangerous substances	The materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chris Crampton
Controller - Unitary EMEA, Finance and Accounting



Allegion (UK) Limited
35 Rocky Lane
Aston
Birmingham
B6 5RQ

30th August 2021