

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

“BRITON 376 (See ANNEX A) **377** (See ANNEX B) **378** (See ANNEX C) **379** (See ANNEX D)
BOSS PH.902 (See Annex A) **PH.903** (See Annex B) **PH.901** (See Annex C)
PH.904 (See Annex D) **Series” Panic Exit Devices**

Intended use: For use on single and double leaf escape panic doors, including fire resisting doors
 & Locked doors on escape routes.

Essential Characteristics	Performance	Harmonised Technical Specification
Mechanical Test Evidence : 145924 / 145925 / 172273 / 178803 / 178821 / 180622 / 181094 / 182650-A/B/D/E/J / WIL 363384 / WIL 420071 / WIL 420093 / WIL 420136-2 / WIL 430256 / WIL 438044 / WIL 513902 & WIL 541969 Fire Test Evidence : WF332444 / WF 393476 / WF 417359 / WF 417361 / WF 417363 & WF 422916 Iss 2		
Clause 4.2.1 Ability to release (for doors on panic routes) Release function Panic exit device mounting Exposed edges and corners Double doorset Single doorset Bar installation Bar length Bar projection Bar end Operating bar face Test rod Door face gap Accessible gap Door free movement Top vertical bolt Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement	< 1 sec Pass > 0,5 mm Pass Pass Pass Z < 150 mm > 60% W < 100mm or 150mm Pass > 18 mm Pass > 25 mm Pass Pass Pass – (Annex A & Annex B Only) Pass Pass – (Annex A & Annex B Only) Door mass ≤ 200 Kg, door height ≤ 2500 mm, door width ≤ 1300 mm Pass < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N Grade 2	EN 1125:2008
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on panic routes) Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance –Horizontal bar Abuse resistance –Vertical rod Final examination	Grade 3 : 96 h Operating forces at -10 C° and +60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 1 000 N 500 N – (Annex A & Annex B Only) < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Essential Characteristics	Performance	Harmonised Technical Specification
Clause 4.2.1 Self closing ability C (for fire/smoke doors on panic routes) Re-engagement force	< 50 N	EN 1125:2008
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on panic routes) Durability Re-engagement force	Grade 7: 200 000 cycles < 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on panic routes) Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies.	
Clause 4.1.25 Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Product Codes	Single Door (Standard Keeper)	Double Door (Standard Keepers)	Approved with Alternate Strike or Keeper			
			378 DDS	376 MDS	378 MDS	379 MDS
ANNEX A						
Briton 376	✓	✓	-----	✓	-----	-----
Briton 376D	✓	✓	-----	✓	-----	-----
Briton 376.SE with 380/1011/SE	✓	✓	-----	✓	-----	-----
Briton 376.SE with 370PLTM	✓	✓	-----	✓	-----	-----
Briton 376.SE with 376/1021/SE	✓	✓	-----	✓	-----	-----
Briton 376.SE with 376/1021/SE and 370PLTM	✓	✓	-----	✓	-----	-----
Briton 376M	✓	✓	-----	✓	-----	-----
Briton 376M.SE with 370PLTM	✓	✓	-----	✓	-----	-----
Boss PH.902	✓	✓	-----	✓	-----	-----
ANNEX B						
Briton 377	-----	✓	✓	✓	✓	-----
Briton 377D	-----	✓	✓	✓	✓	-----
Briton 377M	-----	✓	✓	✓	✓	-----
Boss PH.903	-----	✓	✓	✓	✓	-----
ANNEX C						
Briton 378	✓	✓	✓	-----	✓	-----
Briton 378D	✓	✓	✓	-----	✓	-----
Briton 378.SE with 376/1021/SE	✓	✓	✓	-----	✓	-----
Briton 378M	✓	✓	✓	-----	✓	-----
Boss PH.901	✓	✓	✓	-----	✓	-----
ANNEX D						
Briton 379.N	✓	✓	-----	-----	-----	✓
Briton 379D.N	✓	✓	-----	-----	-----	✓
Briton 379.N.SE With 380/1011/SE	✓	✓	-----	-----	-----	✓
Briton 379.N with 379/1021/SE	✓	✓	-----	-----	-----	✓
Briton 379M.N	✓	✓	-----	-----	-----	✓
Boss PH.904	✓	✓	-----	-----	-----	✓
Accessories						
Model Number		Description				
Briton 1413.LE		Lever outside access device (Suitable for use with all devices)				
Briton 1413.KE		Knob outside access device (Suitable for use with all devices)				
Briton 1413.BP		Retrofit Plate (Suitable for use with all devices)				
Boss OAD.900LE		Lever outside access device (Suitable for use with all devices)				
Boss OAD.900KE		Knob outside access device (Suitable for use with all devices)				
Briton 9260 Codelock		Lever outside access device (Suitable for use with 376 / 377 & 378 Only)				
Rim Cylinder		for use with 378 products only				

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Placed on the market under the name of:

**Allegion (UK) Ltd
35 Rocky Lane
Birmingham
West Midlands
B6 5RQ
United Kingdom**

and produced in the manufacturing plant:

E014110-19

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1125: 2008

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **26/10/2020** and revised **18/07/2025** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **02/04/2026**

ERO Project Reference: **ERO 034621 P2747**



**Pascal Coget
European Certification –General Manager**

CSF408-NL 8.0