

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

“BRITON 372 (See ANNEX A) 389 (See ANNEX B) 1438 (See ANNEX C) & BOSS PH.905 (See ANNEX A) PH.907 (See ANNEX B) PH.906 (See ANNEX C) Push Pad Range” Emergency Exit Devices

Intended use: For use on single leaf escape route doors, including fire resisting control doors.

| Essential Characteristics | Performance | Harmonised Technical Specification |
|--|---|------------------------------------|
| Mechanical Test Evidence : 145924 / 145925 / 172273 / 178803 / 178803 / 178821 / 180257 / 180622 / 181094 / 182650/C/F/H/I&K / 196439 / WIL 427612 / WIL 438045 / WIL 518140 & WIL 541969 Fire Test Evidence : WF 332444 / WF 393476 / WF 417359 / WF 417361 / WF417363 & WF 422916 Iss 2 | | |
| Clause 4.2.1 Ability to release (for doors on escape routes) Release function Push pad Single doorset Double doorset Exposed edges and corners Push pad installation Operating element projection Operating element face (Push Pad) Push pad operating gap Test rod Push pad release operation Accessible gap Door free movement Top vertical bolt Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement | < 1 sec Pass Pass Pass Pass Z < 250 mm W < 100mm Pass Pass Pass Pass Pass Pass Pass Pass – (Annex A Only) Pass Pass – (Annex A Only) Door mass ≤ 200 Kg, door height ≤ 2500 mm, door width ≤ 1300 mm Pass Type B < 150 N Grade 4 | EN 179 : 2008 |
| Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes) Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance – Push Pad Abuse resistance –Vertical rod Final examination | Grade 3 : 96 hours Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 500 N & 1000N 500 N – (Annex A Only) Type B < 150 N | |

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

| Essential Characteristics | Performance | Harmonised Technical Specification |
|--|---|------------------------------------|
| Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes) Re-engagement force | < 50 N | EN 179 : 2008 |
| Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes) Durability Re-engagement force | Grade 7: 200 000 cycles < 50 N | |
| Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes) Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements | Grade B: Suitable for use on fire/smoke door assemblies. | |
| Clause 4.1.25 Control of Dangerous substances | If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. | |

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

| Product Codes | Single Door (Standard Keeper) | Double Door (Standard Keepers) | Approved with Alternate Strike or Keeper | | | |
|-----------------------------|----------------------------------|---|--|---------|---------|---------|
| | | | 378 DDS | 376 MDS | 378 MDS | 379 MDS |
| ANNEX A | | | | | | |
| Briton 372 | √ | √ | ----- | √ | ----- | ----- |
| Briton 372M | √ | √ | ----- | √ | ----- | ----- |
| Briton 372D | √ | √ | ----- | √ | ----- | ----- |
| Briton 372.SE with 370PLTM | √ | √ | ----- | √ | ----- | ----- |
| Briton 372M.SE with 370PLTM | √ | √ | ----- | √ | ----- | ----- |
| Boss PH.905 | √ | √ | ----- | √ | ----- | ----- |
| | | | | | | |
| ANNEX B | | | | | | |
| Briton 389.N | √ | √ | ----- | ----- | ----- | √ |
| Briton 389M.N | √ | √ | ----- | ----- | ----- | √ |
| Boss PH.907 | √ | √ | ----- | ----- | ----- | √ |
| ANNEX C | | | | | | |
| Briton 1438 | √ | √ | √ | ----- | √ | ----- |
| Briton 1438M | √ | √ | √ | ----- | √ | ----- |
| Briton 1438D | √ | √ | √ | ----- | √ | ----- |
| Boss PH.906 | √ | √ | √ | ----- | √ | ----- |
| Accessories | | | | | | |
| Model Number | | Description | | | | |
| Briton 1413.LE | | Lever outside access device (Suitable for use with all devices) | | | | |
| Briton 1413.KE | | Knob outside access device (Suitable for use with all devices) | | | | |
| Briton 1413.BP | | Retrofit Plate (Suitable for use with all devices) | | | | |
| Boss OAD.900LE | | Lever outside access device (Suitable for use with all devices) | | | | |
| Boss OAD.900KE | | Knob outside access device (Suitable for use with all devices) | | | | |
| Briton 9260 Codelock | | Lever outside access device (Suitable for use with 372 & 1438 range only) | | | | |
| Rim Cylinder | | For use 1438 products only | | | | |

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

Placed on the market under the name of:

**Allegion (UK) Ltd
35 Rocky Lane
Birmingham
West Midlands
B6 5RQ
United Kingdom**

and produced in the manufacturing plant:

E014110-19

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 179: 2008

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **26/08/2009** and revised on **18/07/2025** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **02/04/2026**

ERO Project Reference: **ERO 034621 P2748**



**Pascal Coget
European Certification –General Manager**

CSF408-NL 8.0