

## Declaration of Performance

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**No. AL-0000401607**

1. Unique identification code of the product-type:

**Briton 2003 Overhead Door Closer**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Briton 2003**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1154: 1996: A1: 2002/AC:2006  
Notified Certification body No.2812 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR- AD0013**

8. European Technical Assessment:

**N/A**

9. Declared performance

| Essential characteristics      | Performance  | Harmonised technical specification |
|--------------------------------|--|------------------------------------|
| Self closing.<br>5.2.1 General |  | EN 1154: 1996: A1: 2002/AC:2006    |
| Application                    | Door Mount Pull Side (Fig 1)<br>Transom Mount Push Side (Fig 61) |                                    |
| 5.2.2 Durability               | 500,000  |                                    |
| 5.2.3 Closing moment           | Pass size 3  |                                    |
| 5.2.4 Opening moment           | Pass size 3  |                                    |

|   |   |   |
|---|---|---|
| <b>5.2.5 Efficiency</b><br><b>5.2.6 Closing time</b><br><b>5.2.7 Angles of operation</b><br><b>5.2.8 Overload performance</b><br><b>5.2.9 Temperature dependence</b><br><b>5.2.10 Fluid leakage</b><br><b>5.2.11 Damage</b><br><b>5.2.12 Latch control</b><br><b>5.2.13 Backcheck</b><br><b>5.2.14 Delayed Action</b><br><b>5.2.15 Adjustable closing force</b><br><b>5.2.16 Zero position (double action doors only)</b><br><br><b>5.2.18 Fire / smoke doors</b> | <b>&gt;55% size 3</b><br><b>Pass</b><br><b>Grade 4, 180°</b><br><b>Pass</b><br><b>-15°C to +40°C</b><br><b>Pass</b><br><b>Pass</b><br><b>Pass</b><br><b>NPD</b><br><b>NPD</b><br><b>NPD</b><br><b>NPD</b><br><br><b>Grade 1: suitable for use on fire/smoke doors (≥EN3 )</b> |   |
| <b>Essential characteristics</b>  | <b>Performance</b>  | <b>Harmonised technical specification</b> |
| <b>Durability of Self Closing</b><br><b>5.2.2 Durability</b><br><b>5.2.17.1 corrosion</b><br><b>5.2.17.2 corrosion</b><br><br><u><b>Dangerous Substances</b></u><br><u><b>Annex ZA3</b></u>   | <b>500,000</b><br><b>Grade 3 (96 hours)</b><br><b>Pass</b><br><br><br><b>Pass</b>   | <b>EN 1154: 1996: A1: 2002/AC:2006</b>    |

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox  
UK General Manager



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

24th April 2025

## Declaration of Performance

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**No. AL-0000401607**

2. Unique identification code of the product-type:

**Briton 2003 Overhead Door Closer**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Briton 2003**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1154: 1996: A1: 2002/AC:2006  
Notified Certification body No.2812 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR- AD0013**

8. European Technical Assessment:

**N/A**

9. Declared performance

| Essential characteristics                | Performance                      | Harmonised technical specification |
|--|----------------------------------|------------------------------------|
| Self closing.<br>5.2.1 General           |                                  | EN 1154: 1996: A1: 2002/AC:2006    |
| Application                              | Transom Mount Push Side (Fig 61) |                                    |
| 5.2.2 Durability<br>5.2.3 Closing moment | 500,000<br>Pass size 3           |                                    |

|  |   |   |
|--|---|---|
| 5.2.4 Opening moment<br>5.2.5 Efficiency<br>5.2.6 Closing time<br>5.2.7 Angles of operation<br>5.2.8 Overload performance<br>5.2.9 Temperature dependence<br>5.2.10 Fluid leakage<br>5.2.11 Damage<br>5.2.12 Latch control<br>5.2.13 Backcheck<br>5.2.14 Delayed Action<br>5.2.15 Adjustable closing force<br>5.2.16 Zero position (double action doors only)<br><br>5.2.18 Fire / smoke doors | Pass size 3<br>>55% size 3<br>Pass<br>Grade 3, >105°<br>Pass<br>-15°C to +40°C<br>Pass<br>Pass<br>Pass<br>NPD<br>NPD<br>NPD<br>NPD<br><br>Grade 1: suitable for use on fire/smoke doors (≥EN3 ) |   |
| <b>Essential characteristics</b>   | <b>Performance</b>  | <b>Harmonised technical specification</b> |
| Durability of Self Closing<br>5.2.2 Durability<br>5.2.17.1 corrosion<br>5.2.17.2 corrosion<br><br><u><b>Dangerous Substances</b></u><br><u><b>Annex ZA3</b></u>  | 500,000<br>Grade 3 (96 hours)<br>Pass<br><br><br>Pass   | EN 1154: 1996: A1: 2002/AC:2006           |

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox  
UK General Manager



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

24th April 2025

## Declaration of Performance

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**No. AL-0000401607**

1. Unique identification code of the product-type:

**Briton 2003 Overhead Door Closer**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Briton 2003**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1154: 1996: A1: 2002/AC:2006  
Notified Certification body No.2812 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR-AD0013**

8. European Technical Assessment:

**N/A**

9. Declared performance

| Essential characteristics  | Performance  | Harmonised technical specification     |
|--|--|--|
| <b>Self closing</b><br><b>5.2.1 General</b><br><br><b>Application</b><br><br><b>5.2.2 Durability</b><br><b>5.2.3 Closing moment</b><br><b>5.2.4 Opening moment</b> | <b>Parallel Arm (Fig 66)</b><br><br><br><b>500,000</b><br><b>Pass size 3</b><br><b>Pass size 3</b> | <b>EN 1154: 1996: A1: 2002/AC:2006</b> |

|   |   |   |
|---|---|---|
| 5.2.5 Efficiency                                | >55% size 3   |   |
| 5.2.6 Closing time                              | Pass  |   |
| 5.2.7 Angles of operation                       | Grade 3, >102°  |   |
| 5.2.8 Overload performance                      | Pass  |   |
| 5.2.9 Temperature dependence                    | -15°C to +40°C  |   |
| 5.2.10 Fluid leakage                            | Pass  |   |
| 5.2.11 Damage                                   | Pass  |   |
| 5.2.12 Latch control                            | Pass  |   |
| 5.2.13 Backcheck                                | Pass  |   |
| 5.2.14 Delayed Action                           | NPD   |   |
| 5.2.15 Adjustable closing force                 | Pass  |   |
| 5.2.16 Zero position (double action doors only) | NPD   |   |
| 5.2.18 Fire / smoke doors                       | Grade 1: suitable for use on fire/smoke doors (≥EN3 ) |   |
| <b>Essential characteristics</b>                | <b>Performance</b>                                    | <b>Harmonised technical specification</b> |
| <u><b>Durability of Self Closing</b></u>        |   |   |
| 5.2.2 Durability                                | 500,000   |   |
| 5.2.17.1 corrosion                              | Grade 3 (96 hours)                                    |   |
| 5.2.17.2 corrosion                              | Pass  | EN 1154: 1996: A1: 2002/AC:2006           |
| <u><b>Dangerous Substances</b></u>              |   |   |
| <u><b>Annex ZA3</b></u>                         | Pass  |   |

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox  
UK General Manager



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

24th April 2025