

Declaration of Performance

CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

No. AL-0000401610

1. Unique identification code of the product-type:

Briton 2003V Overhead Door Closer

Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Briton 2003V

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1154: 1996: A1: 2002/AC:2006 Notified Certification body No.2812 performed the type testing and issued test reports. Certificate of Constancy of Performance - 2812-CPR- AD0168

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Self closing 5.2.1 General		
Application	Door Mount Pull Side (Fig 1)	
	500,000	EN 1154: 1996: A1: 2002/AC:2006
5.2.2 Durability	Pass size 2-4	
5.2.3 Closing moment	Pass size 2-4	
5.2.4 Opening moment	>50% size 2	



5.2.5 Efficiency	>60% size 4	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 4, 180°	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Backcheck	Pass	
5.2.14 Delayed Action	NPD	
5.2.15 Adjustable closing force	Pass	
5.2.16 Zero position (double action	NPD	
doors only)		
5.2.18 Fire / smoke doors	Grade 1: suitable for use on	
	fire/smoke doors (≥EN3)	
Essential characteristics	Performance	Harmonised technical specification
Durability of Self Closing		
5.2.2 Durability	500,000	
5.2.17.1 corrosion	Grade 3 (96 hours)	
5.2.17.2 corrosion	Pass	EN 1154: 1996: A1: 2002/AC:2006
Dangerous Substances		
Annex ZA3	Pass	

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox UK General Manager

Pedettago

Allegion (UK) Limited 35 Rocky Lane Aston

Birmingham B6 5RQ

24th April 2025



Declaration of Performance

CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

No. AL-0000401610

2. Unique identification code of the product-type:

Briton 2003V Overhead Door Closer

Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Briton 2003V

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1154: 1996: A1: 2002/AC:2006 Notified Certification body No.2812 performed the type testing and issued test reports. Certificate of Constancy of Performance - 2812-CPR- AD0168

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Self closing 5.2.1 General		
Application	Transom Mount Push (Fig 61)	
		EN 1154: 1996: A1: 2002/AC:2006
5.2.2 Durability	500,000	
5.2.3 Closing moment	Pass size 2-4	
5.2.4 Opening moment	Pass size 2-4	



5.2.5 Efficiency	>50% size 2	
_	>60% size 4	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 3, >105°	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Backcheck	Pass	
5.2.14 Delayed Action	NPD	
5.2.15 Adjustable closing force	Pass	
5.2.16 Zero position (double action	NPD	
doors only)		
5.2.18 Fire / smoke doors	Grade 1: suitable for use on	
	fire/smoke doors (≥EN3)	
Essential characteristics	Performance	Harmonised technical specification
		·
Durability of Self Closing		
5.2.2 Durability	500,000	
5.2.17.1 corrosion	Grade 3 (96 hours)	
5.2.17.2 corrosion	Pass	EN 1154: 1996: A1: 2002/AC:2006
3.2.17.2 COITOSION	1 455	LN 1134. 1990. A1. 2002/A0.2000
Dangerous Substances		
Annex ZA3	Pass	
Tilliex 270	1 455	

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox UK General Manager

Pestettago

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

24th April 2025



Declaration of Performance

CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

No. AL-0000401610

1. Unique identification code of the product-type:

Briton 2003V Overhead Door Closer

Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Briton 2003V

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1154: 1996: A1: 2002/AC:2006 Notified Certification body No.2812 performed the type testing and issued test reports. Certificate of Constancy of Performance - 2812-CPR- AD0168

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Self closing 5.2.1 General		
Application	Parallel Arm (Fig 66)	
5.2.2 Durability 5.2.3 Closing moment 5.2.4 Opening moment	500,000 Pass size 1-3 Pass size 1-3	EN 1154: 1996: A1: 2002/AC:2006



5.2.5 Efficiency	>50% size 1	
	>55% size 3	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 3, 105°	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Backcheck	Pass	
5.2.14 Delayed Action	NPD	
5.2.15 Adjustable closing force	Pass	
5.2.16 Zero position (double action	NPD	
doors only)		
5.2.18 Fire / smoke doors	Grade 1: suitable for use on	
	fire/smoke doors (≥EN3)	
Essential characteristics	Performance	Harmonised technical specification
Durability of Self Closing		
5.2.2 Durability	500,000	
5.2.17.1 corrosion	Grade 3 (96 hours)	
5.2.17.2 corrosion	Pass	EN 1154: 1996: A1: 2002/AC:2006
Dangerous Substances		
Annex ZA3	Pass	
- Thirty - I to	. 400	

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox UK General Manager

Pedettago

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

24th April 2025