

## Declaration of Performance

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

No. AL-0000402583

1. Unique identification code of the product-type:

**Briton 4801.304, 4802.304, 4803.304,  
Briton Y4801.304, Y4802.304, Y4803.304,**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Briton 4801.304, 4802.304, 4803.304,  
Briton Y4801.304, Y4802.304, Y4803.304,**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire/smoke compartmentation doors fitted with door closing devices (to enable such doors to close reliably and thus achieve self closing in the event of fire)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1935: 2002/AC:2003  
Notified testing laboratory No.2812 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR-AC5075**

8. European Technical Assessment:

**N/A**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Self-closing Initial friction torque (door mass 120 kg) Static load Load deformation	< 4,0 Nm with door mass 120kg  Passed with a displacement under load: -lateral < 4 mm -vertical < 2 mm	EN 1935:2002/AC:2003

<b>Overload</b>  <b>Shear strength</b>  <b>Hinges for use on fire-resistant and/or smoke-controls doors</b>	and a residual displacement after unloading. -lateral < 0,6 mm -vertical < 0,3 mm  <b>Passed</b>  Passed with a lateral and vertical deformation under loading <3mm Additional lateral and vertical displacement after unloading < 1 mm  Grade 1: suitable for use on fire/smoke resistant door assemblies. 120 Minute Metal doors. (IMM & MM) 30 and 60 minute timber and mineral based assemblies (ITT)	
<b>Durability</b>  <b>Families of hinges with common design feature</b>  <b>Corrosion resistance</b>	Passed a 200 000 cycles test with a maximum wear: -lateral < 0,5 mm -vertical < 1,0 mm Maximum frictional torque. -after 20 cycles < 4.0 Nm -after the completion of 200 000 cycles < 4.0 Nm  The hinge covered by this DoP is the hinge tested  Grade 4 Neutral Salt Spray (NSS) : 240 h	
<b>Dangerous substances</b>	<b>Pass:</b> the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox  
UK General Manager



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ  
24th April 2025